



# R3000 Quad robustOS

Industrial Cellular VPN Router with 4 Ethernet Ports  
 4 Eth + 1 RS-232/1 RS-485 + 1 USB Host



## INTRODUCTION

The Robustel Industrial Cellular VPN Router with 4 Ethernet Ports (R3000 Quad) is a rugged cellular router offering state-of-the-art mobile connectivity for machine to machine (M2M) applications.

R3000 Quad is a powerful router developed from **RobustOS**, a Robustel self-developed and Linux-based operating system which is designed to be used in Robustel devices. The RobustOS includes basic networking features and protocols providing customers with a very good user experience. Meanwhile, Robustel offers a **Software Development Kit (SDK)** for partners and customers to allow additional customization by using C, Python or Java. It also provides rich **Apps** to meet fragmented IoT market demands.

Robustel is a leading global industrial IoT/M2M hardware and solution provider. Since its establishment in 2010 in Guangzhou, China, Robustel has been focusing on designing and manufacturing industrial cellular routers, gateways, modems, cloud platforms and E2E solutions. In order to support global business in more than 100+ countries and regions, Robustel has set up local offices in Germany, Australia, the Netherlands, the UK, Japan and Hong Kong.


## KEY FEATURES

- > The feature *Link Manager* supporting WWAN1, WWAN2, Ethernet WAN, WLAN WAN link backup and ICMP detection
- > The option *Backup Mode* supporting cold, warm and load balancing
- > RobustOS + SDK + App
- > IPsec/OpenVPN/GRE/L2TP/PPTP/DMVPN
- > Management and maintenance via Web/CLI/SNMP/RobustLink Cloud
- > Robust industrial design (9 to 60V DC, desktop or wall mounting or DIN rail mounting)

## CERTIFICATIONS

CE, EAC, TRA, RCM, RoHS, WEEE

## APPLICATION EXAMPLE



## SPECIFICATIONS

### Cellular Interface

Number of antennas	2 (MAIN + AUX)
Connector	SMA female
SIM	2 (3 V & 1.8 V)

### Ethernet Interface

Number of ports	4 x 10/100 Mbps, 4 x LAN or 3 x LAN + 1 x WAN
Magnet isolation protection	1.5 KV

### WiFi Interface (Optional)

Number of antennas	1
Connector	RP-SMA male
Standards	802.11a/b/g/n, supporting AP and Client modes
Frequency bands	2.412 - 2.484 GHz (2.4 GHz ISM band) 4.910 - 5.825 GHz (5 GHz ISM band)
Security	Open, WPA, WEP
Encryption	AES, TKIP, WEP64
Data speed	Up to 150 Mbps

### GPS/GLONASS Interface (Optional)

Number of antennas	1
Connector	SMA female with 50 ohms impedance
Acquisition sensitivity	GPS: greater than -148 dBm GLONASS: greater than -145 dBm
Horizontal position accuracy	GPS: 2.5 m GLONASS: 2.6 m
Protocol	NMEA-0183 v4.10

### Serial Interface (Software selectable)

Number of ports	1 x RS-232 or 1 x RS-485
Connector	7-pin 3.5 mm female socket with lock
Baud rate	300bps to 230400bps

### Others

Reset button	1 x RST
SD	1 x Micro SD interface
Expansion	1 x USB 2.0 host up to 480 Mbps
CLI	1 x CLI interface

LED indicators	1 x RUN, 1 x PPP, 1 x USB, 1 x RSSI, 1 x NET, 1 x SIM
Built-in	RTC, Watchdog, Timer

### Software (Basic features of RobustOS)

Network protocols	PPP, PPPoE, TCP, UDP, DHCP, ICMP, NAT, HTTP, HTTPS, DNS, ARP, NTP, SMTP, Telnet, VLAN, SSH2, DDNS, etc.
VPN tunnel	IPsec, OpenVPN, GRE
Firewall	DMZ, anti-DoS, Filtering (IP/Domain name/MAC address), Port Mapping, Access Control
Management	Web, CLI, SMS
Serial port	Transparent, TCP Client/Server, UDP, Modbus RTU Gateway

### App Center (Available Apps for RobustOS)

Apps*	L2TP, PPTP, DMVPN, RobustVPN, VRRP, QoS, SNMP, Language, RobustLink
-------	---------------------------------------------------------------------

\*Request on demand. For more Apps please visit [www.robustel.com](http://www.robustel.com).

### Power Supply and Consumption

Connector	3-pin 5 mm female socket with lock
Input voltage	9 to 60V DC
Power consumption	Idle: 100 mA@12 V Data link: 400 mA (peak) @12 V

### Physical Characteristics

Ingress protection	IP30
Housing & Weight	Metal, 570 g
Dimensions	125 x 104 x 43.5 mm
Installations	Desktop or wall mounting and 35 mm DIN rail mounting

### EMC

EMI	EN 55022: 2006/A1: 2007 (CE & RE) Class B
EMS	IEC 61000-4-2 (ESD) Level 3 IEC 61000-4-3 (RS) Level 4 IEC 61000-4-4 (EFT) Level 4 IEC 61000-4-5 (Surge) Level 4 IEC 61000-4-6 (CS) Level 3 IEC 61000-4-8 (M/S) Level 4

## ORDERING INFORMATION

Model	R3000-Q3PB	R3000-Q4LB	R3000-QLB
Router Type	HSPA+ Router	LTE Router	Wireline Router
Air Interface	GSM/GPRS/EDGE/HSDPA/HS UPA/HSPA+	GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/HSPA+/DC-HSPA+/TD-SCD MA/CDMA (CDMA 1X/EVDO)/FDD LTE/TDD LTE	--
Frequency Bands 4G*	--	AU: B1/B3/B5/B7/B8/B28, B40 EU: B1/B3/B7/B8/B20/B28/B31, B38/B40 US: B2/B4/B5/B13/B17/B25, B41 JP: B1/B3/B8/B9/B18/B19/B21/B28, B41 CN: B1/B3, B38/B39/B40/B41	--
3G	B1/B2/B4(AWS)/B5/B8/B19	WCDMA/HSDPA/HSUPA/HSPA+/DC-HSPA+: B1/B2/B5/B6/B8/B9/B19 TD-SCDMA: B34/B39 CDMA (CDMA 1X/EVDO): R0/A BC0/BC1/BC10	--
2G	850/900/1800/1900 MHz	850/900/1800/1900 MHz	--
Operating Environment	-40 to +75 °C 5 to 95% RH	-40 to +75 °C 5 to 95% RH	-40 to +75 °C 5 to 95% RH

\*For more information about 4G frequency bands in different countries, please contact your Robustel sales representative.